

## AMENDMENTS TO THE CLAIMS

Please replace the current version of the claims with the following rewritten version:

1. – 8. (Cancelled)

9. (Currently Amended) An optical cursor control device having a light concentrating pad and an optical pointing device moved on the light concentrating pad by an operator, the light concentrating pad comprising:

an optical wave guide;

a lower reflecting plate attached to a bottom of the optical wave guide for upwardly reflecting light introduced into the optical wave guide;

an upper transparent plate attached to a top of the optical wave guide for passing the light reflected from the lower reflecting plate, the upper transparent plate having an opening therein for exposing the optical waveguide, and a surface of an entrance of the opening being parallel to a surface of the lower reflecting plate in direct contact with the optical wave guide;

side reflecting plates attached to a portion of sides of the optical wave guide for reflecting the light in the optical wave guide; and

a light concentrating plate attached to an edge of the lower reflecting plate and separated from the upper transparent plate, wherein the light concentrating plate is disposed on another portion of the sides of the optical wave guide, extending diagonally and upwardly from the lower reflecting plate to the upper transparent plate, contacting the upper transparent plate adjacent to the opening along a line, the opening of the upper transparent plate being disposed directly on the light concentrating plate, and reflects external light into the optical wave guide through another portion of the sides of the optical wave guide.

10. (Original) The optical cursor control device according to claim 9, wherein the upper transparent plate includes regular patterns drawn on a surface thereof.

11. (Previously Presented) The optical cursor control device according to claim 9, wherein the optical pointing device comprises:

a case including a lower panel, the lower panel having an opening;

an optical sensor mounted inside the case for sensing reflected light introduced into the case through the opening; and

a printed circuit board for processing a signal outputted from the optical sensor to generate an output signal that corresponds to a position of the case.

12. (Previously Presented) The optical cursor control device according to claim 11, wherein the optical pointing device further comprises:

a switch module disposed on the printed circuit board; and

a button disposed at the top surface of the case to turn on or off the switch module.

13. – 16. (Cancelled)

17. (Previously Presented) The optical cursor control device according to Claim 9, further comprising: a light source emitting a light toward the light concentrating plate, wherein the light concentrating plate reflects the light from the light source into the optical wave guide.

18. (Currently Amended) An optical cursor control device including a worktable and an optical pointing device moved on the worktable by an operator, the optical pointing device comprising:

a case;

a light guide disposed at a sidewall of the case, one portion of the light guide being a protrusion upwardly protruding from the sidewall of the case, the one portion of the light guide being exposed to an external environment outside the case, an other portion of the light guide extending from the sidewall of the case to an interior of the case by a predetermined length, the other portion of the light guide being exposed to an internal environment inside the case, ~~introducing external lights into the case and including a protrusion outwardly protruded from the case,~~ the light guide directly accepting the external lights through the protrusion to obliquely irradiate lights penetrating the light guide onto a surface of the worktable through an opening formed in a lower panel of the case;

an optical sensor disposed in the case and over the opening to detect lights reflecting from the surface of the worktable; and

a printed circuit board with electronic parts processing an output signal of the optical sensor to generate an output signal that corresponds to a position of the case.

19. (Previously Presented) The optical cursor control device according to Claim 18, wherein the light guide includes a light concentrating surface located at the protrusion to directly accept the external lights and an illuminating surface located opposite the protrusion to irradiate the lights penetrating the protrusion onto the surface of the worktable.

20. (Previously Presented) The optical cursor control device according to Claim 19, wherein the illuminating surface has an area smaller than that of the light concentrating surface.

21. (Previously Presented) The optical cursor control device according to Claim 18, further comprising a light emitting device installed in the case, wherein the light emitting device is automatically or manually turned on and lights from the light emitting device are irradiated onto the surface of the worktable through the opening.

22. (Previously Presented) The optical cursor control device according to Claim 18, further comprising:

a switch module mounted on the printed circuit board; and

a button disposed on a top of the case to turn on or turn off the switch module.

23. (Currently Amended) An optical cursor control device having a worktable and an optical pointing device moved on the worktable by an operator, the optical pointing device comprising:

a case;

an optical sensor disposed in the case;

a light guide disposed at a sidewall of the case, and including first and second surfaces respectively on predetermined portions of the light guide~~that comprises a,~~

the first surface of the light guide being spaced away from the case and that acceptings  
light reflecting from a surface of the[[a]] worktable adjacent to the case, and

the[[a]] second surface of the light guide being adjacent to the case and that introduces  
the light penetrating the light guide onto an optical sensor in the case, the first and second  
surfaces including one optically functioning material, and a remaining portion of the light guide  
including optically different functioning material from the first and second surfaces; ~~the light~~  
~~guide being disposed at a sidewall of the case for introducing external lights the light reflecting~~  
~~from the surface of the worktable into the case, the light guide including a protrusion outwardly~~  
~~protruded from the case, the light guide accepting lights reflecting from the worktable adjacent to~~  
~~the case through the protrusion to irradiate lights penetrating the light guide onto the optical~~  
sensor; and

a printed circuit board with electronic parts processing an output signal of the optical sensor to generate an output signal that corresponds to a position of the case.

24. and 25. (Cancelled)

26. (Previously Presented) The optical cursor control device according to Claim 23, wherein the light guide further comprises light concentrators disposed at the first and second surfaces, and the light concentrators increase intensities of the lights passing through the light concentrators.

27. (Previously Presented) The optical cursor control device according to Claim 26, wherein the light concentrators are convex lenses.

28. (Previously Presented) The optical cursor control device according to Claim 23, further comprising:

a switch module mounted on the printed circuit board; and  
a button disposed on a top of the case to turn on or off the switch module.

29. (Previously Presented) The optical cursor control device according to Claim 23, wherein the first surface and the second surface are parallel to each other.